



Schedule of Scope to Certificate of Approval Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 1 of 8

TESTD PARTS

Fixed capacitor, Fixed resistor, Potentiometer, Varistor, Thermistor, Connector, Relay, Switch, Printed circuit board, Semiconductor Devices, Semiconductor Integrated Circuit and Optical Component

ENVIRONMENTAL TEST

IEC 60068-2-1:2007	Cold
IEC 60068-2-2:2007	Dry heat
IEC 60068-2-11:1981	Salt mist
IEC 60068-2-14:2009	Change of temperature
IEC 60068-2-20:2008	Test methods for solderability and resistance to soldering heat of devices with leads
IEC 60068-2-30:2005	Damp heat, cyclic (12+12-hour cycle)
IEC 60068-2-38:2009	Composite temperature/humidity cyclic test
JIS C 60068-2-42:1993	Sulphur dioxide test for contacts and connections
JIS C 60068-2-43:1993	Hydrogen sulphide test for contacts and connections
IEC 60068-2-45:1980	Immersion in cleaning solvents
JIS C 60068-2-52:2000	Salt mist, cyclic (sodium chloride solution)
IEC 60068-2-54:2006	Soldering. Solderability testing by the wetting balance method
JIS C 60068-2-58:2016	Test methods for solderability, resistance to dissolution of metallization and to soldering heat of SMD
IEC 60068-2-60:2015	Flowing mixed gas corrosion test
IEC 60068-2-66:1994	Damp heat, steady state (unsaturated pressurized vapour)
IEC 60068-2-78:2012	Damp heat, steady state
MIL STD 202H	Test method standard electronic and electrical component parts
MIL STD 883K	Test method standard microcircuits

This schedule is only valid in conjunction with the referenced Certificate of Approval
This approval and any schedule(s) may only be reproduced in full.
This approval is not transferable and remains the property of the issuing body.
The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 2 of 8

MECHANICAL TEST

IEC 60068-2-6:2007	Vibration (sinusoidal)
IEC 60068-2-21:2006	Robustness of terminations and integral mounting devices
IEC 60068-2-27:2008	Shock
IEC 60068-2-31:2008	Rough handling shocks, primarily for equipment-type specimens
IEC 60068-2-53:2010	Tests and Guidance: Combined climatic (temperature/humidity) and dynamic (vibration/shock) tests

STRESS TEST

JEITA ED-4701/302:2013

Environmental and endurance test methods for semiconductor devices
(Stress test I-2)

Test method 304A	Human body model electrostatic discharge (HBM/ESD)
Test method 305C	Charged device model electrostatic discharge (CDM/ESD)
Test method 306B	Latch-up

JEITA ED-4701/600:2013

Environmental and endurance test methods for semiconductor devices
(Specific test for discrete semiconductors)

Test method 601	Power cycling test (Molding type)
Test method 602	Power cycling test (Non-molding type/short time)
Test method 603	Power cycling test (Non-molding type/long time)

This schedule is only valid in conjunction with the referenced Certificate of Approval
This approval and any schedule(s) may only be reproduced in full.
This approval is not transferable and remains the property of the issuing body.
The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 3 of 8

LED OPTICAL CHARACTERISTIC TEST

JIS C 7801:2009	Measuring methods of lamps for general lighting
JIS C 8152-1:2012	Photometry of white light emitting diode for general lighting — Part 1: LED packages
JIS C 8152-2:2012	Photometry of white light emitting diode for general lighting — Part 2: LED modules and LED light engines
JIS C 8105-5:2011	Luminaires — Part 5: Gonio-photometric method

OTHER TEST

Failure Analysis, Construction Analysis, Elemental Analysis, Thermal Analysis and Internal Gas Analysis of Electronic component, including Electrical Analysis, NDE (Non-destructive Engineering), Physical Analysis, Chemical Analysis and Sample Preparation (Decap, X-section, etc),

This schedule is only valid in conjunction with the referenced Certificate of Approval
This approval and any schedule(s) may only be reproduced in full.
This approval is not transferable and remains the property of the issuing body.
The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 4 of 8

MEASUREMENT RANGE

Passive component

Type / Part name	Measurable property value	Measuring range
Fixed capacitor	(1)Voltage endurance (DC)	: AC,DC 0 ~ 5kV
	(2)Insulation resistance	: $5 \times 10^5 \Omega \sim 10^{14} \Omega$
	(3)leakage current	: $1 \times 10^{-3} \sim 10^{-11} \text{ A}$
	(4)Capacitance	: 18pF ~ 1F*
	(5)Dielectric loss tangent(D factor)	: 10* min
	(6)Impedanc	: $1 \Omega \sim 10^* \text{ M}\Omega$
	(7)Temperature properties and gap of the capacitance.	: Temperature range -40°C ~ +150°C Attention : * The mark varies according to measurement frequency.
Fixed resistor	(1)Resistance value	: $1 \Omega \sim 100 \text{ M}\Omega$
	(2)Resistance temperature properties and gap of the resistance level.	: Temperature range -55°C ~ +150°C
	(3)Voltage factor	: $\pm 0.02\% / \text{V}$
	(4)Insulation resistance	: $5 \times 10^5 \Omega \sim 2 \times 10^{14} \Omega$
	(5)Voltage endurance	: AC,DC 0 ~ 5kV
Variable resistor *potentiometer	(1)Resistance value	: $1 \Omega \sim 100 \text{ M}\Omega$
	(2)Mutual deviations	: $\pm 3\%$
	(3)Resistance temperature properties and gap of the resistance level.	: Temperature range -40°C ~ +150°C
	(4)Insulation resistance	: $5 \times 10^5 \Omega \sim 10^{14} \Omega$
	(5)Voltage endurance	: AC,DC 0 ~ 5kV
	(6)Rotational noise	: Noise voltage 1mV
	(7)Intensive contact resistance	: 1 mΩ
Varistor	Voltage at reference current	: 1500V(1mA min)
Thermistor	(1)resistance value	: $1 \Omega \sim 1000 \text{ k}\Omega$
	(2)The thermistor fixed number	: Temperature range -50°C ~ +300°C

This schedule is only valid in conjunction with the referenced Certificate of Approval
 This approval and any schedule(s) may only be reproduced in full.
 This approval is not transferable and remains the property of the issuing body.
 The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
 Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
 4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 5 of 8

MEASUREMENT RANGE

Active component part [Individual semiconductor part]

Type / Part name	Measurable property value	Measuring range
Transistor *Bipolar	(1)Collector-base breakdown voltage	:1V ~ 1.5kV
	(2)Collector-emitter breakdown voltage	:1V ~ 1.5kV
	(3)Emitter base breakdown voltage	:100V min
	(4)Collector base interception electric current	:1nA ~ 100mA
	(5)Collector emitter interception electric current	:1nA ~ 100mA
	(6)Emitter base interception electric current	:1nA ~ 100mA
	(7)The collector emitter saturation voltage	:7V min ($I_C < 17A$)
	(8)DC current gain	:25 ~ 25,000 ($I_C < 17A$)
Transistor *Field effect form	(1)Gate source breakdown voltage	:1V ~ 1.5kV
	(2)Gate leak electric current	:1pA ~ 100mA
	(3)Drain current	:1nA ~ 1A
	(4)The gate cut-off voltage	: ~ 100V
	(5)The drain source saturation voltage	:7V min ($I_D < 17A$)
Diode *Small signal *I rectify a small electric current *Constant voltage *Small electric current switching	(1)Forward voltage	:7V min ($I_F < 17A$)
	(2)Reverse current	:1na ~ 100mA ($V_R < 100V$)
	(3)Breakdown voltage	:1V ~ 1.5kV
	(4)Zener voltage	:100V min
	(5)Dynamic resistance	:50Ω max
	(6)Temperature coefficient	:Temperature range -55°C ~ +150°C
Thyristor *3 reverse-blocking terminals *Small electric current	(1)Off electric current	:1mA ($V_L < 1kV$)
	(2)Reverse current	:1na ~ 1mA ($V_L < 1kV$)
	(3)ON-state voltage	:7V ($I_{TM} < 10A$)
	(4)Gate trigger	:1000V min
	(5)Holding current	:10A ($V_{TM} < 7V$)

This schedule is only valid in conjunction with the referenced Certificate of Approval
 This approval and any schedule(s) may only be reproduced in full.
 This approval is not transferable and remains the property of the issuing body.
 The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
 Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
 4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 6 of 8

MEASUREMENT RANGE

Active component part Semiconductor Devices [Integrated circuit]

Type / Part name	Measurable property value	Measuring range
TTL IC	(1)The high-level output voltage	:±30V
	(2)The low-level output voltage	:±30V
	(3)The input clamp voltage	:±30V
	(4)High-level input electric current	:±300mA
	(5)Low-level input electric current	:±300mA
	(6)Output short circuit current	:±300mA
	(7)High-level power supply electric current	:±300mA
	(8)Low-level power supply electric current	:±300mA
CMOS IC	(1)The high-level output voltage	:±30V
	(2)The low-level output voltage	:±30V
	(3)The high-level input voltage	:±20V
	(4)Low-level input electric current	:±20V
	(5)High-level output electric current	:±300mA
	(6)Low-level output electric current	:±300mA
	(7)Static consumption electric current	:±300mA
	(8)Input current	:±300mA
Analog semiconductor integrated circuit *Monolithic op-amp	(1)Input-offset voltage	:10μV ~ 128mV
	(2)Input offset current	:20pA ~ 16μA
	(3)Input bias current	:20pA ~ 16μA
	(4)Open loop voltage gain	:0.1V/mV ~ 1.2V/μV
	(5)The max power voltage	:10mV ~ 50V
	(6)Power consumption	:5mW ~ 6.4W
	(7)Common mode rejection ratio	:38 ~ 116dB
	(8)Supply voltage rejection ratio	:38 ~ 116dB
	(9)Aspect input voltage range	:100mV ~ 25V
	(10)Slew rate	:0.1 ~ 125V/μS

This schedule is only valid in conjunction with the referenced Certificate of Approval
This approval and any schedule(s) may only be reproduced in full.
This approval is not transferable and remains the property of the issuing body.
The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval
Independent Testing Laboratory
 IECQ Certificate No.: IECQ-L JQAJP 13.0002
 CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S Rev No.: 8 Revision Date: 2020/05/15 Page 7 of 8

MEASUREMENT RANGE

Mechanical device

Type / Part name	Measurable property value	Measuring range
Connector (Electronic equipment use)	(1)Insulationresistanc	: $5 \times 10^5 \Omega \sim 2 \times 10^{14} \Omega$
	(2)Withstand voltage	:AC,DC 0 ~ 5kV
	(3)Contact resistance under low voltage, the low electric current	:1m Ω ~ 100 Ω
	(4)Chattering of the contact.	:1 μ sec max
Relay (Small form for control)	(1)Withstand voltage	:AC,DC 0 ~ 5kV
	(2)Insulation resistance	: $5 \times 10^5 \Omega \sim 2 \times 10^{14} \Omega$
	(3)Direct current resistance of the coil	:1 Ω ~ 10k Ω
	(4)Contact resistance	:1m Ω ~ 100 Ω
	(5)Operating voltage	:1V max
	(6)Must-release voltage	:1V max
	(7)Operation time	:1msec max
	(8)Recovery time	:1msec max
	(9)Bounces of the point of contact	:1 μ sec max
	(10)Chattering of the point of contact	:1 μ sec max
Switch (Electronic equipment use)	(1)Contact resistance	:1m Ω ~ 100 Ω
	(2)Insulation resistance	: $5 \times 10^5 \Omega \sim 2 \times 10^{14} \Omega$
	(3)Withstand voltage	: AC,DC 0 ~ 5kV
	(4)Electrostatic capacity	:18pF ~ 1F
	(5)Change of the contact resistance	:1m Ω max
Printed circuit board	(1)Resistance of the plating part of the conductor and through hall part.	:1m Ω ~ 1000 Ω
	(2)Withstand voltage	: AC,DC 0 ~ 5kV
	(3)Insulation resistance	: $5 \times 10^5 \Omega \sim 10^{14} \Omega$

This schedule is only valid in conjunction with the referenced Certificate of Approval
 This approval and any schedule(s) may only be reproduced in full.
 This approval is not transferable and remains the property of the issuing body.
 The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
 Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
 4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan



Schedule of Scope to Certificate of Approval

Independent Testing Laboratory

IECQ Certificate No.: IECQ-L JQAJP 13.0002

CB Certificate No.: JQAQ0002-001-T

Schedule Number: IECQ-L JQAJP 13.0002-S

Rev No.: 8

Revision Date: 2020/05/15

Page 8 of 8

MEASUREMENT RANGE

Optical component

Type / Part name	Measurable property value	Measuring range
Luminescent diode (It is for indication.)	(1)Forward voltage (2)Reverse current (3)Luminous intensity(Relative value)	:7V min :1mA min :----
LED (It is for illumination.)	1.Integrating sphere (1)Total luminous flux[lm] (2)Color temperature[K] (3)Chromaticity coordinate (4)The number of the color rendering evaluations	:Measurable wavelength range 350nm ~ 1000nm In sunshine: min 32lm ~ :---- :---- :Ra,R1 ~ R14
	2.The light distribution measurement. (1)Light distribution curve (2)Light intensity(Reference)	:Measurable wavelength range 360nm ~ 830nm :Photometric distance 2m ~ 12m, :Photometric distance Luminous intensity :2.0m: 9 ~ 3,680,000[cd] :3.0m: 20 ~ 8,200,000[cd] :6.0m: 83 ~ 33,000,000[cd] :12m : 330 ~ 132,000,000[cd]
	(3)Color temperature (4)Chromaticity coordinate (5)The number of the color rendering evaluations	: ---- :---- : Ra,R1 ~ R14

This schedule is only valid in conjunction with the referenced Certificate of Approval
 This approval and any schedule(s) may only be reproduced in full.
 This approval is not transferable and remains the property of the issuing body.
 The Status and authenticity of this approval and any schedule(s) may be verified by visiting the
 Official IECQ Website. www.iecq.org



Japan Quality Assurance Organization (JQA)
 4-4-4, Minamiosawa, Hachioji-shi, Tokyo 192-0364 Japan